

# 2010 KLX™ 250S

OFFROAD

**Kawasaki**  
Let the good times roll.™



\* Canadian model may not be exactly as shown



LIME GREEN

## KLX 250S

When the pavement ends, the fun doesn't have to stop if you're riding the Kawasaki KLX250S. Lights, turn signals and all you need to ride on the street are here, but the KLX250S's heart belongs in the dirt. With its 249cc liquid-cooled single, long-travel suspension and rugged steel frame, this lightweight machine lets you access the best of both worlds.

## KEY FEATURES

- 1 COMPACT ENGINE DESIGN IS LIGHTWEIGHT AND HIGH REVVING, WITH A BROAD TORQUE CURVE
- 2 MULTI-FUNCTION DIGITAL INSTRUMENTATION
- 3 QUICK AND EASY PUSH-BUTTON ELECTRIC STARTING
- 4 LIGHTWEIGHT HIGH CAPACITY RADIATORS
- 5 KLX-SPEC HANDLEBAR FOR A MORE RELAXED POSITION AND EFFORTLESS CONTROL
- 6 GOOD MASS CENTRALIZATION FOR SUPERIOR HANDLING



FOR MORE INFORMATION VISIT [www.kawasaki.ca](http://www.kawasaki.ca)

# KLX™ 250S



\*Canadian model may not be exactly as shown

EBONY

## Specifications

<b>Engine type</b>	Four-stroke, DOHC, 4-valve single
<b>Displacement</b>	249 cc
<b>Bore x stroke</b>	72.0 x 61.2 mm
<b>Compression ratio</b>	11.0:1
<b>Cooling</b>	Liquid, twin radiators
<b>Fuel system</b>	Keihin CVK34 carburetor
<b>Ignition</b>	Digital DC-CDI
<b>Starting</b>	Electric
<b>Transmission</b>	6-speed
<b>Final drive</b>	Chain
<b>Frame</b>	Perimeter High-tensile steel
<b>Rake/trail</b>	27.5°/110 mm (4.3 in.)
<b>Front suspension/wheel travel</b>	43 mm inverted cartridge fork with 16-way compression and rebound damping adjustment / 260 mm (10.2 in.)
<b>Rear suspension/wheel travel</b>	UNI-TRAK® with Adjustable Preload, 16-Way Compression and Rebound Damping Adjustment/230 mm (9.1 in.)
<b>Tire, front</b>	3.00-21
<b>Tire, rear</b>	4.60-18
<b>Brakes, front</b>	250 mm semi-floating petal disc with 2-piston hydraulic caliper
<b>Brakes, rear</b>	240 mm petal disc with single-piston hydraulic caliper
<b>Wheelbase</b>	1440 mm (56.7 in.)
<b>Ground clearance</b>	280 mm (11.0 in.)
<b>Seat height</b>	885 mm (34.8 in.)
<b>Curb weight*</b>	135 kg (297.6 lbs.)
<b>Fuel capacity</b>	7.0 litres (1.54 gal.)
<b>Warranty</b>	6 month

\*Includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90% of capacity) and tool kit (if supplied)

## SAFE RIDING'S MORE FUN

Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a helmet, eye protection, and proper apparel. Never ride under the influence of drugs or alcohol. KLX models are for closed-course competition only. Riding is more fun on a well-maintained motorcycle...follow the instructions in your owner's manual. Remember, riding safe is smart.

## ACCESSORIES

1. Wheel Chock
2. Steadymate Cinchtite Tie Down Straps
3. Soft Loop
4. Work Pad



CLICK FOR DETAILS

Take an in-depth tour @ [www.kawasaki.ca/klx](http://www.kawasaki.ca/klx)

TO VIEW OUR COMPLETE ACCESSORY CATALOGUE VISIT: [kawasaki.ca/accessories](http://kawasaki.ca/accessories)

UP TO THREE YEARS ADDITIONAL COVERAGE



with the Good Times™ Protection Plan\*  
For more information visit: [kawasaki.ca/good-times-protection-plan](http://kawasaki.ca/good-times-protection-plan)

\*Depending on the program purchased.

Kawasaki subscribes to the guidelines of Tread Lightly!, a program dedicated to protecting the great outdoors through education and fostering responsible enjoyment of public lands.

treadlightly!  
LEAVING A GOOD IMPRESSION



\*Fuel Efficient

Vehicles that have a fuel efficiency rating under 5.5L/100km.



The specifications mentioned here apply to and have been achieved by production models under standard operating conditions. We intend only to give a fair description of the vehicle and its performance capabilities but these specifications may not apply to every machine supplied for sale. Kawasaki Heavy Industries, Ltd. reserves the right to alter specifications without prior notice. Equipment illustrated and specifications may vary to meet individual markets. Available colours may vary by market.