

2010 KX™ 250F

MOTOCROSS

Kawasaki
Let the good times roll.™



LIME GREEN

KX250F

Kawasaki's 2009 KX 250F motocrosser had a victorious year, winning on the track and topping its class in numerous enthusiast magazine shootouts. But in the volatile world of racing, it's a constant challenge to stay on top. To ensure it continues its podium-topping tradition, Kawasaki fine-tuned the light handling KX250F for 2010. The engineers capitalized on its solid foundation, with refinements focused on increasing performance and longevity. The result of their labours will help the KX250F add to its ever-growing trophy collection.

KEY FEATURES

- 1 **HIGH REVVING ENGINE
FACTORY TUNED FOR
HIGH-END PERFORMANCE**
- 2 **ALL NEW PISTON DESIGN**
- 3 **IMPROVED HANDLING
CHARACTERISTICS**
- 4 **IMPROVED REAR WHEEL
TRACTION**
- ◀ **NEW "HOT START" SYSTEM**
- ◀ **ENHANCED DURABILITY
AND RELIABILITY**



FOR MORE INFORMATION VISIT www.kawasaki.ca

KX™250F



Specifications

Engine type	Four-stroke single with DOHC and 4-valves
Displacement	249cc
Bore x stroke	77.0 x 53.6 mm
Cooling	Liquid
Fuel system	Keihin FCR-MX37 carburetor
Compression ratio	13.2:1
Ignition	Digital AC-CDI
Starting	Primary Kick
Transmission	5-speed
Final drive	Chain
Frame	Aluminum perimeter
Rake/trail	27.4°/118.6 mm (4.7 in.)
Front suspension/ wheel travel	47 mm inverted Showa twin-chamber telescopic fork with 16-way compression and rebound damping/315 mm (12.4 in.)
Rear suspension/ wheel travel	UNI-TRAK® linkage system Showa shock with 13-way low-speed and 2-turn high-speed compression damping, 17-way rebound damping and fully adjustable spring preload/310 mm (12.2 in.)
Tire, front	80/100-21
Tire, rear	100/90-19
Brakes, front	Single semi-floating 250 mm petal disc with dual piston caliper
Brakes, rear	Single 240 mm petal disc with single-piston caliper
Wheelbase	1470 mm (57.9 in.)
Seat height	955 mm (37.6 in.)
Ground clearance	340 mm (13.4 in.)
Curb weight*	105.0 kg (231.5 lbs.)
Fuel capacity	8 litres (1.76 gal.)

* Includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90% of capacity) and tool kit (if supplied)

SAFE RIDING'S MORE FUN

Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a helmet, eye protection, and proper apparel. Never ride under the influence of drugs or alcohol. KX models are for closed-course competition only. Riding is more fun on a well-maintained motorcycle...follow the instructions in your owner's manual. Remember, riding safe is smart.

ACCESSORIES

1. Wheel Chock
2. Steadymate Cinchtite Tie Down Straps
3. Soft Loop
4. Work Pad



[CLICK FOR DETAILS](#)

Take an in-depth tour @ www.kawasaki.ca/kx

TO VIEW OUR COMPLETE ACCESSORY CATALOGUE VISIT: kawasaki.ca/accessories

Kawasaki Racing news

Race preparation techniques

Sign up for Team Green Contests

Interact with Team Green Multi-media.

Be part of the team and log onto: teamgreennews.ca

Kawasaki subscribes to the guidelines of Tread Lightly!, a program dedicated to protecting the great outdoors through education and fostering responsible enjoyment of public lands.

treadlightly!
LEAVING A GOOD IMPRESSION



The specifications mentioned here apply to and have been achieved by production models under standard operating conditions. We intend only to give a fair description of the vehicle and its performance capabilities but these specifications may not apply to every machine supplied for sale. Kawasaki Heavy Industries, Ltd. reserves the right to alter specifications without prior notice. Equipment illustrated and specifications may vary to meet individual markets. Available colours may vary by market.