

2010 KX™ 450F

MOTOCROSS

Kawasaki
Let the good times roll.™



LIME GREEN



KX450F

Already ranked at the top of its class in numerous enthusiast magazine shootouts, the 2010 KX450F receives a number of engine and chassis updates to ensure its winning potential. Its precise aluminum frame, premium suspension components and expert-tuned settings are designed to deliver superb high-speed stability, enabling racers to capitalize on its amazing engine performance.

KEY FEATURES

- 1 IMPROVED SUSPENSION ACTION
- 2 OPTIONAL USER ECU SETTING TOOL ALLOWS RACERS TO REPROGRAM THE ECU'S DATA MAPS TO SUIT RIDER PREFERENCE
- 3 IMPROVED ENGINE RESPONSE AT LOW-MID RPM
- 4 BATTERY-LESS FUEL INJECTION WITH HIGH PERFORMANCE ECU
- 5 LIGHTER HANDLING
- 6 REVAMPED CLUTCH FEELING FOR INCREASED CONTROL

FOR MORE INFORMATION VISIT www.kawasaki.ca

KX™ 450F



Specifications

| | |
|--------------------------------------|---|
| Engine type | Four-stroke single with DOHC and 4-valves |
| Displacement | 449cc |
| Bore x stroke | 96.0 x 62.1 mm |
| Cooling | Liquid |
| Fuel system | Digital fuel injection with 43 mm Keihin throttle body |
| Compression ratio | 12.5:1 |
| Ignition | Digital DC-CDI |
| Starting | Primary Kick |
| Transmission | 5-speed |
| Final drive | Chain |
| Frame | Aluminum perimeter |
| Rake/trail | 26.7°/116 mm (4.6 in.) |
| Front suspension/wheel travel | 48 mm inverted Kayaba AOS with DLC coated sliders, 22-position compression and 20-position rebound dampening adjustment/315 mm (12.4 in.) |
| Rear suspension/wheel travel | UNI-TRAK® linkage system and Kayaba shock with 22-position low-speed and stepless high-speed compression dampening, 22-position rebound dampening and fully adjustable spring preload/315 mm (12.4 in.) |
| Tire, front | 90/100-21 |
| Tire, rear | 120/80-19 |
| Brakes, front | Single semi-floating 250 mm petal disc with dual piston caliper |
| Brakes, rear | Single 240 mm petal disc with single-piston caliper |
| Wheelbase | 1480 mm (58.3 in.) |
| Seat height | 965 mm (38.0 in.) |
| Ground clearance | 340 mm (13.4 in.) |
| Curb weight* | 113.6 kg (250.4 lbs.) |
| Fuel capacity | 7 litres (1.54 gal.) |

* Includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90% of capacity) and tool kit (if supplied)

SAFE RIDING'S MORE FUN

Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a helmet, eye protection, and proper apparel. Never ride under the influence of drugs or alcohol. KX models are for closed-course competition only. Riding is more fun on a well-maintained motorcycle...follow the instructions in your owner's manual. Remember, riding safe is smart.

ACCESSORIES

1. Wheel Chock
2. Steadymate Cinchtite Tie Down Straps
3. Soft Loop
4. Work Pad



CLICK FOR DETAILS

Take an in-depth tour @ www.kawasaki.ca/kx

TO VIEW OUR COMPLETE ACCESSORY CATALOGUE VISIT: kawasaki.ca/accessories

Kawasaki Racing news

Race preparation techniques

Sign up for Team Green Contests

Interact with Team Green Multi-media.

Be part of the team and log onto: teamgreennews.ca

Kawasaki subscribes to the guidelines of Tread Lightly!, a program dedicated to protecting the great outdoors through education and fostering responsible enjoyment of public lands.

treadlightly!
LEAVING A GOOD IMPRESSION



The specifications mentioned here apply to and have been achieved by production models under standard operating conditions. We intend only to give a fair description of the vehicle and its performance capabilities but these specifications may not apply to every machine supplied for sale. Kawasaki Heavy Industries, Ltd. reserves the right to alter specifications without prior notice. Equipment illustrated and specifications may vary to meet individual markets. Available colours may vary by market.